BLACKTOP CRACK FILLER

SINCE SAKRETE 1936

◆ The Pro's Choice Since 1936

Sakrete® Black Top Crack Filler is designed for repairing cracks in black top to help prevent damaging water penetration.

Features:

- For cracks up to 1/2" (12 mm) wide
- For crack repairs prior to applying sealer
- Helps to prevent water intrusion which can cause undermining and damage to asphalt.
- Packaged with easy pour spout
- Ready to use

Use For:

- Driveways
- Walk ways
- Parking lots
- Ramps
- For horizontal asphalt crack repairs

Yield/Coverage:

Container Size	Yield
1 gal (3.8 L)	Will fill approximately 160 ft (12 m) of 1/4" (6 mm) wide by 1/2" (12 mm) deep crack

NOTE: The yield is approximate and does not allow for waste and spillage.

Technical Data:

DIVISION 32
Flexible Pavement Repair – 32 01 17

Color: Black

Preparation:

For best results all materials should be stored between 40°F (4°C) and 80°F (27°C) 24 hours prior to installation.

1. Surfaces to be repaired must be sound, dimensionally stable, and clean.
2. Clean all dirt and loose materials from the crack(s).
3. Dampen the crack, but do not leave any standing water.
4. Deep cracks should be filled with sand or backer rod to within 1/2" (12 mm) of the surface.

Application:

1. Shake container well.
2. Pour material into the crack then smooth the surface with a spatula.
3. Do not fill cracks that are deeper than 1/2" (12 mm) in one application.
4. If more than one layer is required, wait 5 days between applications.

Mixing:

1. No mixing required. Shake container well.

Curing:

1. Full cure can take up to 5 days depending on weather conditions.
2. Keep traffic off the area during this time.
3. If it is necessary to open area to traffic before the Sakrete Black Top Crack Filler is fully cured, sprinkling sand on the patch will help to prevent tracking.
4. If a driveway sealer is to be applied, wait 5 days after applying the Black Top Crack Filler before applying the driveway sealer.

VOC: <50 g/l

Precautions:

Air, mix and substrate temperatures should be between 40°F (4°C) and 90°F (32°C) and no rain in the forecast within 24 hours of application. For applications outside this range of temperatures and conditions, contact Sakrete Technical Service.

- Colder temperatures or higher humidity conditions will retard set times
- Protect from freezing for 48 hours after application.

NOTE: STORE SAKRETE BLACK TOP CRACK FILLER IN AN AREA THAT WILL PREVENT IT FROM FREEZING

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).
KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

SAKRETE® and the background design are registered trademarks of SAKRETE of North America LLC, Charlotte, NC 28217 • ©2006. SAKRETE® is manufactured under license from SAKRETE of North America LLC.
For current and complete product information, contact SAKRETE Technical Services toll-free at 866-725-7383 or visit Sakrete.com.