

The Pro's Choice Since 1936



**SAKRETE®**

# Blacktop Sealer

The most economical SAKRETE® coal tar grade. Offers good bonding and a jet black finish.

## SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

## DIRECTIONS:

1. Clean surface to be sealed. To avoid peeling and flaking of seal coat, remove all dirt, loose and foreign materials.
2. Scrape off oil spots and scrub with strong detergent. Rinse thoroughly. Flush off entire area using hard stream of water.
3. Stir product to uniform consistency before application. Liquid may have brown appearance but dries black.
4. Begin at highest area of pavement. Pour a 6-10 inch wide ribbon of sealer across the driveway.
5. Use rubber blade of brush/ squeegee applicator to distribute product evenly. Then draw brush through applied area with long, even strokes to achieve uniform, thin coating without puddling in surface voids. Tap brush on uncoated area to remove excess before final brush stroke to blend "stops and starts".
6. Repeat steps 4 and 5, working toward lower areas.

APPLY ONE COAT ONLY. DO NOT APPLY THICK/HEAVY COATING. EXCESSIVE MATERIAL CAN CAUSE TRACKING. Best results come from a single, thin application.

## CURING:

Best results are achieved with temperatures of 70°F to 90° F during application. Cooler temperatures and/or high humidity may lengthen curing time. DO NOT APPLY IF NIGHT TIME TEMPERATURES WILL FALL BELOW 50°F, OR RAIN IS PREDICTED WITHIN 24 HOURS OF APPLICATION. Irreparable damage to the curing film may result.

## HELPFUL HINTS:

- In sunny, hot weather, pavements may reach temperatures high enough to "cook dry" sealer. Mist area with fine water spray to cool pavement about an hour before sealer application. Sweep out puddles or any standing water. Wait to apply sealer if pavement is still glistening wet. (This step can be skipped if sealer is applied early in the day, before pavement heats up.)
- In cooler weather, do not mist pavement. If practical, apply sealer early in the day to optimize drying during warmer daylight hours.
- Curing time varies with weather conditions. Sealed areas can usually be opened to traffic after 24 hours. Test before use.
- Do not apply to concrete surfaces. Allow new blacktop paving to cure one year before sealcoating.

## REPAIRS PRIOR TO SEALCOATING:

Fill cracks up to 1/2" wide with Pourable Crack Filler.  
Fill cracks wider than 1/2" with Trowelable Crack Filler.  
Repair pot holes with All Weather Blacktop Patch. Seal around patched areas so that they may cure with at least 90 days of warm weather before sealing.

## STORAGE:

STORAGE: Store in a tightly closed container off the floor in a dry place. KEEP FROM FREEZING.

## COVERAGE:

Approximately 350–450 square feet per 5 gallon pail. Coverage will vary with surface texture and porosity.

## PACKAGING:

5 Gallon (18.9 L) UPC: 0-50605-00091-2

REV 3-10

The Pro's Choice Since 1936



**SAKRETE®**

# Blacktop Sealer

Contents:

Refined Coal Tar	CAS# 65996-93-2
Kaolin	CAS# 1332-58-7
Silica	CAS# 14808-60-7
Synthetic Polymers	(proprietary)
VOC Limit	500 g/l
Asphalt	CAS# 8052-42-4

## ATTENTION

**THIS CONTAINER HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID OR SOLID), ALL LABELED HAZARDOUS PRECAUTIONS MUST BE OBSERVED. DRIED, WATER-FREE RESIDUES MAY BE COMBUSTIBLE. DO NOT EXPOSE TO OPEN FLAME.**

## WARNING

**EYE AND SKIN IRRITANT CONTAINS COAL TAR PITCH WHICH CAN CAUSE IRRITATION TO EYES AND SKIN. Use in well ventilated areas. Avoid prolonged breathing of vapor or mist. Avoid prolonged or repeated contact with skin, especially skin areas exposed to direct sun. In case of skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. Wearing of gloves, protective clothing and eyewear is recommended. In case of contact with eyes, flush with water. Harmful if swallowed. Keep container closed when not in use.**

## LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies  
866-SAKRETE  
866-725-7383