

The Pro's Choice Since 1936



**SAKRETE**<sup>®</sup>

# Driveway Pro Filled Driveway Sealer

Sakrete<sup>®</sup> Driveway Pro Filled Driveway Sealer is a grit-filled asphalt emulsion, easy stir sealer formula that provides added traction to the blacktop area while resisting gasoline and oil. Including a quick drying additive, Sakrete<sup>®</sup> Driveway Pro Filled Sealer provides a jet black finish that beautifies the surface and is resistant to weathering, ultra-violet light, and wear. Manufactured in a colloid mill for superior consistency and quality.

## SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

## DIRECTIONS:

1. Clean surface to be sealed. To avoid peeling and flaking of seal coat, remove all dirt, loose and foreign materials.
2. Scrape off oil spots and scrub with strong detergent or cover with oil spot primer. Rinse thoroughly. Flush off entire area using hard stream of water if strong detergent is used for cleaning .
3. Stir product to uniform consistency before application. Liquid may have brown appearance but dries black.
4. Begin at highest area of pavement. Pour a 6-10 inch wide ribbon of sealer across the driveway.
5. For application using combo brush/squeegee applicator, use rubber blade of brush/ squeegee applicator to distribute product evenly. Then draw brush through applied area with long, even strokes to achieve uniform, thin coating without puddling in surface voids. Tap brush on uncoated area to remove excess before final brush stroke to blend "stops and starts".
6. Repeat steps 4 and 5 on uncoated areas, working toward lower areas.

**Note:** Best results come from a single, thin application.

APPLY ONE COAT ONLY. DO NOT APPLY THICK/HEAVY COATING. EXCESSIVE MATERIAL CAN CAUSE TRACKING.

## CURING:

Best results are achieved with temperatures of 70°F to 90°F during application. Cooler temperatures and/or high humidity may lengthen curing time. DO NOT APPLY IF NIGHT TIME TEMPERATURES WILL FALL BELOW 50°F, OR RAIN IS PREDICTED WITHIN 24 HOURS OF APPLICATION. Irreparable damage to the curing film may result. Allow coating to receive 2 or more hours exposure to sunlight during drying for best results.

## HELPFUL HINTS:

- In sunny, hot weather, pavements may reach temperatures high enough to "cook dry" sealer. Mist area with fine water spray to cool pavement about an hour before sealer application. Sweep out puddles or any standing water. Wait to apply sealer if pavement is still glistening wet. (This step can be skipped if sealer is applied early in the day, before pavement heats up.)
- In cooler weather, do not mist pavement. If practical, apply sealer early in the day to optimize drying during warmer daylight hours.
- Exposure to sunlight warms pavement surfaces to assist in proper curing.
- Curing time varies with weather conditions. Sealed areas can usually be opened to traffic after 24 hours. Test before use.
- Do not apply to concrete surfaces. Allow new blacktop paving to cure one year before sealcoating.

## REPAIRS PRIOR TO SEALCOATING:

Fill cracks up to 1/2" wide with Sakrete Pourable Crack Filler.

Fill cracks wider than 1/2" with Sakrete Trowelable Crack Filler.

Repair pot holes with Sakrete All Weather Blacktop Patch or Sakrete US Cold Patch.

**Note:** When making repairs using Sakrete All Weather Blacktop Patch or Sakrete US Cold Patch allow 90 days for curing before sealcoating the repair area.

## STORAGE:

STORAGE: Store in a tightly closed container off the floor in a dry place. KEEP FROM FREEZING. Freezing will void warranty.

## COVERAGE:

Approximately 350–450 square feet per 5 gallon pail. Coverage will vary with surface texture and porosity.

## PACKAGING:

5 Gallon (18.9 L)

REV 8-11

The Pro's Choice Since 1936

**SAKRETE®**

# Driveway Pro Filled Driveway Sealer

Contents:

Asphalt	CAS# 8052-42-4
Kaolin	CAS# 1332-58-7
Silica	CAS# 14808-60-7
Synthetic Polymers	(proprietary)
VOC Limit	50 g/l

#### ATTENTION

**THIS CONTAINER HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID OR SOLID), ALL LABELED HAZARDOUS PRECAUTIONS MUST BE OBSERVED. DRIED, WATER-FREE RESIDUES MAY BE COMBUSTIBLE. DO NOT EXPOSE TO OPEN FLAME.**

**WARNING! Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin. FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If irritation persists, get medical attention.**

WARRANTY Sealer is warranted from defects for a period of 5 years from date of purchase when surface is prepared and product is applied according to product label instructions. Since many factors that affect performance of product are beyond seller's control, including but not limited to weather, workmanship, equipment used and prior condition of the substrate, seller will not be responsible for defects from these causes or defects in areas of ponding water, poor drainage or consequential or indirect damages, including snow removal damage. Seller will, if product is deemed defective, with proof of original retail receipt, either replace the goods sold or refund purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. There are no express warranties which extend the description on the face hereof; manufacturer disclaims any implied warranties. This warranty does not include labor costs incurred for original product application, re-application or consequential damage costs. Sakrete® Blacktop Repair products listed on this technical data sheet must be used for repairs. This warranty is only for residential (single family) homes. Commercial parking lot applications are not warranted.

The SAKRETE Companies  
866-SAKRETE  
866-725-7383  
www.sakrete.com