

The Pro's Choice Since 1936



**SAKRETE**<sup>®</sup>

# Flashing Cement

## DESCRIPTION:

Asphalt Mastic Cement for repairing holes and cracks in roofing and for general purpose flashing. Also for use in repairing leaky gutters, troughs, copings, pointing around chimneys and as an adhesive for loose shingles.

## COMPOSITION:

Petroleum asphalt, refined mineral spirits.

## PROPERTIES:

Meets ASTM specification D4586-00 for Asphalt Roof Cement, ASBESTOS-FREE.

## DIRECTIONS:

Thoroughly clean all surfaces. Apply with a knife or trowel to a thickness of 1/8 inch. Heavier applications should be built-up in layers. Allow 12 hours between applications. Apply only in dry conditions, when surface and air temperature is minimum 40° F. Store product in a warm area 24 hours before use when temperature is below 65°F. Use a pointed trowel or putty knife for patching and flashing. DO NOT THIN. Keep container tightly closed when not in use. Tools may be cleaned with mineral spirits. Use caution when using these solvents.

## COVERAGE:

Average of 12 square feet per gallon at 1/8" applied thickness.

## PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00558 0  
4.7 Gallon (21.3 L) UPC: 0 50605 00573 3

## CONTAINS:

ASPHALT CAS #8052-42-4  
MINERAL SPIRITS CAS #8052-41-3  
FIBERS CAS #9004-34-6  
LIMESTONE CAS #1317-65-3  
ATTAPULGITE CAS #12174-11-7  
MAXIMUM VOC IS 300 GRAMS/LITER  
MAXIMUM VOS IS 2.5 POUNDS/GALLON

## CAUTION:

COMBUSTIBLE. CONTAINS MINERAL SPIRITS. DO NOT HEAT. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN.

## ATTENTION:

CONTAINER HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions MUST BE OBSERVED. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

## LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies  
866-SAKRETE  
866-725-7383

REV 3-10