

The Pro's Choice Since 1938

SAKRETE

Foundation Coating

DESCRIPTION:

A cut-back asphalt coating primarily formulated as a damp-proof and protective coating on masonry and metal surfaces. Maximum thickness should never exceed 1/32". SAKRETE® Foundation Coating can be applied as a wood preservative to fence posts below grade. Do not use as a roof saturant. Use SAKRETE® Fibrated Roof Coating. Do not use this product as an aggregate binder for built-up roof applications.

COMPOSITION:

Petroleum asphalt, refined mineral spirits.

PROPERTIES:

Meets ASTM specification D-3019, Type 1, Grade 1.

DIRECTIONS:

All surfaces should be clean and dry. Stir material thoroughly and apply by brush or spray. Store product in a warm area 24 hours before use when temperature is below 65° F. Allow 1 to 2 days between coats in warm weather and 3 to 4 days in cold weather. Tools may be cleaned with mineral spirits. Use caution when using these solvents. Keep container covered when not in use. DO NOT THIN.

COVERAGE:

Will vary depending upon conditions and porosity of surface. Average coverage of 50 square feet per gallon, at 1/32" thickness.

PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00549 8
4.7 Gallon (21.3 L) UPC: 0 50605 00548 1

CONTAINS:

ASPHALT CAS #8052-42-4
MINERAL SPIRITS CAS #8052-41-3
MAXIMUM VOC IS 300 GRAMS/LITER
MAXIMUM VOS IS 2.5 POUNDS/GALLON

CAUTION:

CAUTION: COMBUSTIBLE. CONTAINS MINERAL SPIRITS. DO NOT HEAT. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN.

ATTENTION:

CONTAINER HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions MUST BE OBSERVED. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 3-10