

The Pro's Choice Since 1936

SAKRETE®

Lap Cement

DESCRIPTION:

Semi-mastic liquid adhesive for applying saturated felt and roll roofing materials. Quick-setting, cold applied for applications where hot-mopped installations are not practical. May also be used for blind nailing to eliminate potential nail hole leaks.

COMPOSITION:

Petroleum asphalt, refined mineral spirits and NON-ASBESTOS fibers.

PROPERTIES:

Meets ASTM specification D4479-00 Asphalt Roof Coatings, ASBESTOS-FREE AND ASTM D3019-94, Type III.

DIRECTIONS:

For built-up roof construction, thoroughly clean surface. Fill or cover all holes with metal. Prime porous surfaces such as wood and concrete with a non-fibrated roof and foundation coating. When used as a roof repair coating, thoroughly clean surface, repair holes ¼" or larger with glass or fabric embedded in SAKRETE® Plastic Roof Cement. DO NOT THIN.

APPLICATION:

For built-up roof construction, embed (3) starter felts, 12", 24", 36" wide in (3) layers. Turn down over open edges 3" and up walls 2". Continue to embed 36" wide base sheets lapped 24-¾" horizontally. After asphalt cement has set 30 minutes, roll or broom the felt surface to set the bond and edge laps. For two-ply construction use same process, except one 18" and one 36" starter felts are used, with additional sheets lapped at 19".

COVERAGE:

50 square feet as a ply cement at 1/32" thickness. Apply only in dry conditions, with surface and air temperature at minimum 40° F. Store product in a warm area 24 hours before use when temperatures are below 65°F. Stir well before using. Tools may be cleaned with mineral spirits; use caution when using these solvents.

PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00557 3
4.7 Gallon (21.3 L) UPC: 0 50605 00556 6

CONTAINS:

ASPHALT CAS #8052-42-4
MINERAL SPIRITS CAS #8052-41-3
FIBERS CAS #9004-34-6
ATTAPULGITE CAS #12174-11-7
MAXIMUM VOC IS 300 GRAMS/LITER
MAXIMUM VOS IS 2.5 POUNDS/GALLON

CAUTION:

COMBUSTIBLE. CONTAINS MINERAL SPIRITS. DO NOT HEAT. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN.

ATTENTION:

CONTAINER HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions MUST BE OBSERVED. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 3-10