

The Pro's Choice Since 1936



SAKRETE[®]

Aluminum Roof Coating Premium Metallic Pigmented

DESCRIPTION:

Fibred aluminum coating that provides a heat reflective and protective coating on metal, built-up roofing, modified bitumen, cold process and other roof surfaces.

COMPOSITION:

Petroleum asphalt, aluminum pigment, NON-ASBESTOS fibers and chemical agents for adhesion and waterproofing.

NOTE:

Exposure to strong acids and alkalis will cause discoloration. However, coating will continue to protect.

PROPERTIES:

Meets ASTM specification D4479-00 Asphalt Roof Coatings, ASBESTOS-FREE AND ASTM D3019-94, Type III.

DIRECTIONS:

All surfaces should be clean, dry and free of all rust. Stir thoroughly from bottom of container to uniform consistency before use, lifting any pigment which may have settled. Stir periodically during use to maintain uniform distribution of pigment. Apply only in dry conditions with air and surface temperatures above 40° F. Store product in a warm area 24 hours before use when temperature is below 65°F. Apply with brush or airless spray. Do not apply if rain is expected within 24 hours. Equipment can be cleaned with mineral spirits. Use caution when using these solvents. DO NOT THIN.

COVERAGE:

Average of 50 square feet per gallon, depending upon surface texture and porosity.

PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00560 3
4.7 Gallon (17.8 L) UPC: 0 50605 00559 7

CONTAINS:

ASPHALT CAS #8052-42-4
MINERAL SPIRITS CAS #8052-41-3
ALUMINUM PIGMENT CAS #7429-90-5
FIBERS CAS #9004-34-6
MAXIMUM VOC IS 500 GRAMS/LITER
MAXIMUM VOS IS 4.2 POUNDS/GALLON

CAUTION:

COMBUSTIBLE. CONTAINS MINERAL SPIRITS. DO NOT HEAT. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN.

ATTENTION:

CONTAINER HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions MUST BE OBSERVED. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 8-10