

The Pro's Choice Since 1936



SAKRETE®

Roof Coating

DESCRIPTION:

Recommended for sealing and rejuvenating of built-up and composition old roofs. Restores protective properties destroyed by exposure. Protects against deterioration due to exposure, ensuring greater roof service. May also be used on metal roofs and on concrete decks above or below grade.

COMPOSITION:

Petroleum asphalt, refined mineral spirits,
NON-ASBESTOS fiber.

PROPERTIES:

Meets ASTM specification D4479-00 for Asphalt Roof Coating,
ASBESTOS-FREE.

DIRECTIONS:

All surfaces must be dry, clean and free from any loose or spalling material. Repair holes or tears with SAKRETE® Plastic Roof Cement. Store product in a warm area 24 hours before use when temperature is below 65°F. Stir material thoroughly and apply with roofing brush or wide paint brush. Apply only in dry conditions, with surface and air temperature at minimum 40° F. Tools may be cleaned with mineral spirits. Use caution when using these solvents. Keep container covered when not in use. DO NOT THIN.

COVERAGE:

Will vary depending upon conditions and porosity of surface. Typical coverage will average 25 square feet per gallon.

PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00547 4
4.7 Gallon (21.3 L) UPC: 0 50605 00546 7

CONTAINS:

ASPHALT CAS #8052-42-4
MINERAL SPIRITS CAS #8052-41-3
FIBERS CAS #9004-34-6
ATTAPULGITE CAS #12174-11-7
MAXIMUM VOC IS 300 GRAMS/LITER
MAXIMUM VOS IS 2.5 POUNDS/GALLON

ATTENTION:

**CONTAINER HAZARDOUS
WHEN EMPTIED.** Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions **MUST BE OBSERVED**. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 5-11