

The Pro's Choice Since 1936



**SAKRETE®**

# Wet Surface Roof Cement

## DESCRIPTION:

Fibred asphaltic cement for repairing all types of roof surfaces and for waterproofing and flashing where a heavy duty product is required. Bonding characteristics allow emergency repairs during inclement weather conditions. Repairs leaks in metal, shingles, concrete, flashings, gutters, around chimneys, drains, roof perimeters, etc. Bond will hold in varying temperatures and weather conditions.

## COMPOSITION:

Petroleum asphalt, refined mineral spirits, NON-ASBESTOS fiber and surface acting surfactants.

## PROPERTIES:

Meets ASTM specification D4586-00 for Asphalt Roof cements. ASBESTOS-FREE.

## DIRECTIONS:

Clean all surfaces thoroughly. Although product is treated for bonding to damp surfaces, best results occur when application is made to a dry surface. Store product in a warm area 24 hours before use when temperature is below 65° F. If surface is wet, trowel firmly to insure good adhesion. Apply by trowel to a thickness of 1/8" to surfaces to be treated. Apply liberally in joints, seams or cracks. For large cracks or holes, bridge area with glass or cloth fabric or metal mesh before applying asphaltic cement. DO NOT THIN. Tools may be cleaned with mineral spirits. Use caution when using these solvents.

## COVERAGE:

Will average 12 square feet per gallon at 1/8" applied thickness.

## PACKAGING:

1 Gallon (3.8 L) UPC: 0 50605 00551 1  
4.7 Gallon (21.3 L) UPC: 0 50605 00550 4

## CONTAINS:

ASPHALT CAS #8052-42-4  
MINERAL SPIRITS CAS #8052-41  
FIBERS CAS #9004-34-6  
MAXIMUM VOC IS 300 GRAMS/LITER  
MAXIMUM VOS IS 2.5 POUNDS/GALLON

## CAUTION:

COMBUSTIBLE. CONTAINS MINERAL SPIRITS. DO NOT HEAT. KEEP AWAY FROM OPEN FLAME. KEEP OUT OF THE REACH OF CHILDREN.

## ATTENTION:

CONTAINER HAZARDOUS WHEN EMPTIED. Since emptied containers retain product residues (vapor, liquid or solid), all labeled hazard precautions MUST BE OBSERVED. Do not expose to open flame. Use only in well ventilated area – avoid breathing vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting. Call a physician immediately. (Note to physician: contains Hydrocarbon solvents). In case of fire use water spray, foam, dry chemical or carbon dioxide. See physician if product comes in contact with eyes.

## LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies  
866-SAKRETE  
866-725-7383

REV 3-10