

~	Safety Data Sheetaccording to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.Date of issue: 05/02/2017Revision date: 01/31/2018Version: 1.0	
SECTION 1: Identificati	on	
1.1. Identification		
Product form : Mixtures		
Product name	: Sakrete Finish Coat Gray; Sakrete Finish Coat White; Sakrete Water Resistant Stucco; Sakrete Stucco Base Coat Scratch & Brown	
Product code	: Not available	
1.2. Recommended use	and restrictions on use	
Recommended use	: Various	
1.3. Supplier		
625 Griffith Rd., Ste 100 Charlotte, NC 28217 T 866-725-7383 1.4. Emergency telepho	ne number	
Emergency number	: For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night 1-800-424-9300 [USA] / +1 703-527-3887 [CAN]	
SECTION 2: Hazards id	entification	
	lentification e substance or mixture	
2.1. Classification of the		
2.1. Classification of the GHS-US classification		
2.1. Classification of the GHS-US classification Skin Irrit. 2		
2.1. Classification of the GHS-US classification Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1 Carc. 1A		
2.1. Classification of the GHS-US classification Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1		

GHS-US labeling

Hazard pictograms (GHS-US)	HS05 GHS07 GHS08	
Signal word (GHS-US)	GHS05 GHS07 GHS08 : Danger	
Hazard statements (GHS-US)	 Causes skin irritation Causes serious eye damage May cause an allergic skin reaction May cause cancer May cause respiratory irritation Causes damage to lungs through prolonged or repeated exposure 	
Precautionary statements (GHS-US)	 Obtain special instructions before use Do not handle until all safety precautions have been read and understood. Do not breathe dust Wash hands thoroughly after handling Do not eat, drink or smoke when using this product 	
01/31/2018	EN (English US)	

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Use only outdoors or in a well-ventilated area
Contaminated work clothing must not be allowed out of the workplace
Wear eye protection, face protection, protective clothing, protective gloves
If exposed or concerned: Get medical advice/attention
If on skin: Wash with plenty of water
Take off contaminated clothing and wash it before reuse
If skin irritation or rash occurs: Get medical advice/attention
If inhaled: Remove person to fresh air and keep comfortable for breathing
Call a poison center/doctor if you feel unwell
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
and easy to do. Continue rinsing
Immediately call a poison center/doctor
Store in a well-ventilated place. Keep container tightly closed
Store locked up
Dispose of contents/container to hazardous or special waste collection point, in accordance
with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Cement, portland, chemicals	(CAS-No.) 65997-15-1	20 - 30
Calcium oxide	(CAS-No.) 1305-78-8	20 - 30
Gypsum (Ca(SO4).2H2O)	(CAS-No.) 13397-24-5	20 - 30
Limestone	(CAS-No.) 1317-65-3	20 - 30
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	20 - 30
Calcium hydroxide	(CAS-No.) 1305-62-0	0.5 - 2 ¹
Quartz	(CAS-No.) 14808-60-7	> 1
Chromium, ion (Cr 6+)	(CAS-No.) 18540-29-9	< 0.1**

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

** Hexavalent chromium is included due to dermal sensitivity associated with the component.

¹ Only present in Sakrete Finish Coat Gray/White

SECTION 4: First-aid measures				
4.1. Description of first aid measures				
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.			
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.			
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.			
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.			
4.2. Most important symptoms and effect	cts (acute and delayed)			
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.			
Symptoms/effects after skin contact	Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.			

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3			
Symptoms/effects after eye contact	Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.		
Symptoms/effects after ingestion	May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
4.3. Immediate medical attention and spec	ial treatment, if necessary		
Symptoms may be delayed. In case of accident or if y	ou feel unwell, seek medical advice immediately (show the label where possible).		
SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishin	ig media		
Suitable extinguishing media	Use extinguishing media appropriate for surrounding fire.		
Unsuitable extinguishing media	Do not use water jet.		
5.2. Specific hazards arising from the cher	mical		
Fire hazard :	Products of combustion may include, and are not limited to: oxides of carbon. Oxides of sulfur. Metal oxides.		
Reactivity	No dangerous reactions known under normal conditions of use.		
5.3. Special protective equipment and pre-	cautions for fire-fighters		
Firefighting instructions :	Use water spray or fog for cooling exposed containers.		
Protection during firefighting	Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).		
SECTION 6: Accidental release measu	ires		
6.1. Personal precautions, protective equi	pment and emergency procedures		
General measures :	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.		
6.1.1. For non-emergency personnel No additional information available			
6.1.2. For emergency responders No additional information available			
6.2. Environmental precautions			
Prevent entry to sewers and public waters.			
6.3. Methods and material for containment	t and cleaning up		
	Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter		
	waterways. Use appropriate Personal Protective Equipment (PPE).		
Methods for cleaning up	Vacuum or sweep material and place in a disposal container. Avoid generating dust. Provide ventilation.		
6.4. Reference to other sections			
For further information refer to section 8: "Exposure controls/personal protection"			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
, and the second s	Avoid contact with skin and eyes. Do not swallow. Do not breathe dust. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Good housekeeping is important to prevent accumulation of dust.		
Hygiene measures	Wash contaminated clothing before reuse. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including	any incompatibilities		
Storage conditions :	Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a dry, cool and well-ventilated place.		

SECTION 8: Exposure controls/personal protection			
8.1. Control parameters			
Cement, portland, chemicals (65997-15-1)			
ACGIH	ACGIH TWA (mg/m³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

	chemicals (65997-15-1)			
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)		
IDLH	US IDLH (mg/m ³)	5000 mg/m ³		
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)		
Calcium oxide (130)5-78-8)			
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³		
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³		
IDLH	US IDLH (mg/m ³)	25 mg/m³		
NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³		
Gypsum (Ca(SO4).	2H2O) (13397-24-5)			
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)		
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)		
Limestone (1317-6	5-3)			
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)		
Magnesium oxide	(MgO) (1309-48-4)			
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)		
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)		
IDLH	US IDLH (mg/m ³)	750 mg/m³ (fume)		
Calcium hydroxide	(1305-62-0)			
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³		
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m³		
Quartz (14808-60-7)			
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)		
OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m³		
IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)		
Chromium, ion (Cr 6+) (18540-29-9)				
OSHA	OSHA PEL (TWA) (mg/m ³)	5 µg/m ³		

Appropriate engineering controls

Environmental exposure controls

Ensure good ventilation of the work station.Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties				
9.1. Information on basic physical and chemical properties				
Physical state	: Solid			
Appearance	: No data available			
Color	: No data available			
Odor	: No data available			
Odor threshold	: No data available			
рН	: No data available			
Melting point	: No data available			
Freezing point	: No data available			
Boiling point	: No data available			
Flash point	: No data available			
Relative evaporation rate (butyl acetate=1)	: No data available			
Flammability (solid, gas)	: Not flammable			
Vapor pressure	: No data available			
Relative vapor density at 20 °C	: No data available			
Relative density	: No data available			
Solubility	: No data available			
Partition coefficient n-octanol/water	: No data available			
Auto-ignition temperature	: No data available			
Decomposition temperature	: No data available			
Viscosity, kinematic	: No data available			
Viscosity, dynamic	: No data available			
Explosion limits	: No data available			
Explosive properties	: No data available			
Oxidizing properties	: No data available			
9.2. Other information				
No additional information available				
SECTION 10: Stability and reactivity				
10.1. Reactivity				
No dangerous reactions known under normal conditions of use.				
10.2. Chemical stability				
Stable under normal conditions. Keep dry in storage.				

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Moisture. Incompatible materials.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

11.1. Information on toxicological effective	ts		
cute toxicity : Not classified			
Calcium hydroxide (1305-62-0)			
LD50 oral rat	734	7340 mg/kg	
Skin corrosion/irritation	: Ca	: Causes skin irritation.	
Serious eye damage/irritation	: Ca	uses serious eye damage.	
Respiratory or skin sensitization	: Ma	y cause an allergic skin reaction.	
Germ cell mutagenicity	: Not	classified	
Carcinogenicity	: Ma	y cause cancer.	
Quartz (14808-60-7)			
IARC group		1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status		2 - Known Human Carcinogens	
In OSHA Hazard Communication Carcinoge	n list	Yes	
Chromium, ion (Cr 6+) (18540-29-9)			
IARC group		1 - Carcinogenic to humans	
In OSHA Hazard Communication Carcinogen list		Yes	
In OSHA Specifically Regulated Carcinogen list		Yes	
Reproductive toxicity	: Not	classified	
STOT-single exposure	: Ma	y cause respiratory irritation.	
STOT-repeated exposure	: Causes damage to lungs through prolonged or repeated exposure.		
Aspiration hazard	: Not	: Not classified	
Symptoms/effects after inhalation	: Ma	y cause irritation to the respiratory tract.	
Symptoms/effects after skin contact	ma <u>y</u> inju	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.	
Symptoms/effects after eye contact	incl	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.	
Symptoms/effects after ingestion	: Ma	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
ther information : Likely routes of exposure: ingestion, inhalation, skin and eye.			

12.1.ToxicityEcology - general

: May cause long-term adverse effects in the aquatic environment.

0, 0		
Calcium oxide (1305-78-8)		
LC50 fish 1 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])		
Chromium, ion (Cr 6+) (18540-29-9)		
LC50 fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)	
LC50 fish 2 7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)		

Sakrete Finish Coat Gray/White; Sakrete Water Resistant Stucco; Sakrete Stucco Base Coat Scratch & Brown Persistence and degradability Not established.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.2 Piezooumulative notantial					
12.3. Bioaccumulative potential					
Sakrete Finish Coat Gray/White; Sakrete Water Resistant Stucco; Sakrete Stucco Base Coat Scratch & Brown Bioaccumulative potential Not established.					
Calcium oxide (1305-78-8) BCF fish 1 (no bioaccumulation)					
	Calcium hydroxide (1305-62-0)				
BCF fish 1	(no bioaccumulation)				
12.4. Mobility in soil					
No additional information available					
12.5. Other adverse effects					
Effect on the global warming	: No known effects from this product.				
Other information	: No other effects known.				
SECTION 13: Disposal consideration	S				
13.1. Disposal methods					
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. The generation of waste should be avoided or minimized wherever possible.				
SECTION 14: Transport information					
Department of Transportation (DOT)					
In accordance with DOT					
Not regulated					
SECTION 15: Regulatory information					
15.1. US Federal regulations					
All components of this product are listed, or excl Control Act (TSCA) inventory except for:	luded from listing, on the United States Environme	ental Protection Agency Toxic Substances			
Chromium, ion (Cr 6+)		CAS-No. 18540-29-9			
Gypsum (Ca(SO4).2H2O)		CAS-No. 13397-24-5			
15.2. International regulations					
No additional information available					
15.3. US State regulations					
	ose you to chemicals including quartz and chromi n (Cr 6+), which is known to the State of California mings.ca.gov.				
SECTION 16: Other information					
Date of issue	: 05/02/2017				
Revision date	: 01/31/2018				
Other information	information : None.				
Prepared by	: Nexreg Compliance Inc.	\sim			

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

NEXREG

www.Nexreg.com