

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 Date of issue: 04/08/2015 Revision date: 01/31/2018

Version: 1.0

SECTION 1: Identification of the su	bstance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: Sakrete Concrete Repair Sakrete Mortar Repair
Product code	Not available
1.2. Relevant identified uses of the sub	ostance or mixture and uses advised against
Use of the substance/mixture	: Sealant
1.3. Details of the supplier of the safety	y data sheet
Sakrete of North America 8201 Arrowridge Blvd. Charlotte, NC 28273 T 866-725-7383	
1.4. Emergency telephone number	
Emergency number	: CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identification	
2.1. Classification of the substance or	mixture
GHS-US classification	
Specific target organ toxicity - Repeated expos	ure 1
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	: GHS08
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Causes damage to organs through prolonged or repeated exposure.
Precautionary statements (GHS-US)	: Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Get medical advice/attention if you feel unwell. Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3. Other hazards	
No additional information available.	
2.4. Unknown acute toxicity (GHS US)	
25 percent of the mixture consists of ingredient	s of unknown acute toxicity.
SECTION 3: Composition/informati	on on ingredients
3.1. Substance	
Not applicable.	
3.2. Mixture	



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	45- 65	Not classified.
Titanium dioxide	(CAS No) 13463-67-7	0.05 - 5	Carc. 2 ¹
Stoddard solvent	(CAS No) 8052-41-3	0.05 - 3	Flam. Liq. 3 Skin Irrit. 2 Asp. Tox. 1
Ethylene glycol	(CAS No) 107-21-1	<2	Acute Tox. 4 (Oral) Eye Irrit. 2B STOT RE 1
Quartz	(CAS No) 14808-60-7	<0.1 - 1	Carc. 1A ¹ STOT RE 1 ¹

¹Only applies to airborne particles of respirable size

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	 May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
4.3. Indication of any immediate medic	al attention and special treatment needed
Symptoms may not appear immediately. In case	of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Treat for surrounding material.
Unsuitable extinguishing media	: None known.
5.2. Special hazards arising from the s	ubstance or mixture
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
5.3. Advice for firefighters	
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory
5 5 5	protection (SCBA).
SECTION 6: Accidental release me	asures
	equipment and emergency procedures
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
6.2. Methods and material for containing	
For containment	 Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.
6.3. Reference to other sections	
	ive clothing and equipment and section 13 for advice on waste disposal.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not

Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Hygiene measures : Wash hands before eating, drinking, or smoking. Launder contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool area. Keep from freezing.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Limestone (1317-65-3)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m³
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Titanium dioxide (13463-67-7)		

I itanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)

Stoddard solvent (8052-41-3)			
ACGIH	ACGIH TWA (ppm)	100 ppm	
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³	
OSHA OSHA PEL (TWA) (ppm) 500 ppm			

Ethylene glycol (107-21-1)		
ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³ (aerosol only)
OSHA Not applicable		

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m³)	((10 mg/m3)/(%SiO2+2) TWA (resp)) ((30 mg/m3)/(%SiO2+2) TWA (total)) ((250)/(%SiO2+5) mppcf TWA (resp))

8.2. Exposure controls	
Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves.
Eye protection	: Safety glasses with side shields.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Not normally needed. In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic	c physical and chemical properties
Physical state	: Liquid
Appearance	: Paste-like compound
Colour	: Black or grey
Odour	: Sweet acrylic with slight ammonia odor
Odour threshold	: No data available
рН	: 7.5 - 9
Melting point	: No data available
Freezing point	: < 32 °F (< 0 °C)
Boiling point	: > 200 °F (>93.3 °C)
Flash point	: No data available

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: <1
Flammability (solid, gas)	: Not flammable
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: 25 mm Hg @ 68 °F (20 °C)
Relative density	: No data available
Relative vapour density (air = 1)	: >1
Solubility	: Dispersible
Partition coefficient: n-octanol/water	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. **Other information**

No additional information available.

SECTION 10: Stability and reactivity			
10.1. Reactivity			
No dangerous reaction known under conditions of normal use.			
10.2. Chemical stability			
Stable under normal storage conditions.			
10.3. Possibility of hazardous reactions			
No dangerous reaction known under conditions of	No dangerous reaction known under conditions of normal use.		
10.4. Conditions to avoid			
Heat. Incompatible materials.			
10.5. Incompatible materials			
Strong oxidizers.			
10.6. Hazardous decomposition products			
May include, and are not limited to: oxides of carbo	on.		
SECTION 11: Toxicological information	n		
11.1. Information on toxicological effects			
	Not classified.		
Sakrete Concrete Repair / Sakrete Mortar Rep	air		
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	No data available		
Limestone (1317-65-3)			
LD50 oral rat	6450 mg/kg		
Titanium dioxide (13463-67-7)			
LD50 oral rat > 10000 mg/kg			
Ethylene glycol (107-21-1)			
LD50 oral rat	4000 mg/kg		
LD50 dermal rabbit	9530 μL/kg		
Skin corrosion/irritation : Based on available data, the classification criteria are not met.			
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.		
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.		



Safety Data Sheet

Germ cell mutagenicity :	Based on available data, the classification criteria are not met.
Carcinogenicity :	Based on available data, the classification criteria are not met.
Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans (airborne, unbound particles of respirable size)
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans (airborne, unbound particles of respirable size)
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens (airborne, unbound particles of respirable size)
Reproductive toxicity :	Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure) :	Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure) :	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard :	Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation :	May cause respiratory tract irritation.
	May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
	May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion :	May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
SECTION 12: Ecological information	
12.1. Toxicity	
	May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
Sakrete Concrete Repair / Sakrete Mortar Repa	air
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Sakrete Concrete Repair / Sakrete Mortar Repa	air
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available.	
12.5. Other adverse effects Effect on the global warming :	No known ecological damage caused by this product.
Enection the global warming	The known ecological damage caused by this product.
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste disposal recommendations :	This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
SECTION 14: Transport information	
Department of Transportation (DOT)	
In accordance with DOT.	
Not regulated for transport.	
Additional information	
	No supplementary information available.
Other information :	
	Do not handle until all safety precautions have been read and understood.

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Ethylene glycol (107-21-1)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
SARA Section 313 - Emission Reporting	1.0 %
15.2. US State regulations	
Sakrete Concrete Repair / Sakrete Mortar F	Repair
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
SECTION 16: Other information	
Date of issue:	: 04/08/2015
Other information	: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

