

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 11/27/2018 Revision date: 11/27/2018 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Pro-Mix Concrete

1.2. Recommended use and restrictions on use

Recommended use : Various

1.3. Supplier

Manufacturer

Sakrete of North America 625 Griffith Rd., Ste 100 Charlotte, NC 28217 T 866-725-7383

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2

Eye Dam. 1

Carc. 1A

STOT SE 3

STOT RE 1

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : Causes skin irritation

Causes serious eye damage May cause respiratory irritation

May cause cancer

Causes damage to organs (lungs) through prolonged or repeated exposure

Precautionary statements (GHS US) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection, face protection.

If exposed or concerned: Get medical advice/attention.

If on skin: Wash with plenty of water

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing

Call a poison center or doctor if you feel unwell

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Immediately call a poison center or doctor

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation

11/27/2018 EN (English US) Page 1

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Quartz	(CAS-No.) 14808-60-7	30 - 40
Cement, portland, chemicals	(CAS-No.) 65997-15-1	20 - 30

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

First-aid measures after skin contact

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eve contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation

: May cause irritation to the respiratory tract.

Symptoms/effects after skin contact

: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Symptoms/effects after eye contact

: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion

: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recomm

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

11/27/2018 EN (English US) 2/6

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain spill,

: Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Minimize generation of

dust.

Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not swallow. Avoid contact with skin and eyes. Good housekeeping is important to prevent accumulation of dust. Do not breathe dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

> 10 mg/m³ (total dust) 5 mg/m³ (respirable dust)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)

NIOSH

0.025 mg/m³ (respirable particulate matter) 50 µg/m³					
50 ug/m³					
00 kg/					
Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.					
OSHA Annotated Table Z-3 Mineral Dusts					
50 mg/m³ (respirable dust)					
0.05 mg/m³ (respirable dust)					
Cement, portland, chemicals (65997-15-1)					
Portland cement					
1 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)					
Pulm func; resp symptoms; asthma					
ACGIH 2017					
15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)					
50 mppcf					
Table Z-3. CAS No. source: eCFR Table Z-1.					
OSHA Annotated Table Z-3 Mineral Dusts					
5000 mg/m³					

11/27/2018 EN (English US) 3/6

NIOSH REL (TWA) (mg/m3)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.2. Appropriate engineering controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable waterproof gloves

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection:

Wear suitable waterproof protective clothing

Respiratory protection:

A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Powder

Color : No data available
Odor : No data available
Odor threshold : No data available

pH : 12 - 13

: No data available Melting point Freezing point : No data available Boiling point : No data available : No data available Flash point Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : Not flammable Vapor pressure : No data available Relative vapor density at 20 °C : No data available : No data available Relative density Solubility No data available Partition coefficient n-octanol/water : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic No data available **Explosion limits** : No data available : No data available Explosive properties

9.2. Other information

Oxidizing properties

VOC content, wt. %: 0%, Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

11/27/2018 EN (English US) 4/6

: No data available

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.2. Chemical stability

Stable under normal conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

pH: 12 - 13

Serious eye damage/irritation : Causes serious eye damage.

pH: 12 - 13

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

tuartz (14808-60-7)		
IARC group	1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status	Known Human Carcinogens	
In OSHA Hazard Communication Carcinogen list	Yes	

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May

Specific target organ toxicity – repeated

exposure

: May cause respiratory irritation.

Causes damage to organs (lungs) through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact

: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous,

prolonged contact with skin. Handling can cause dry skin.

Symptoms/effects after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

 No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

11/27/2018 EN (English US) 5/6

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.2. Persistence and degradability

Pro-Mix Concrete	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Pro-Mix Concrete		
Bioaccumulative potential	Not established.	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

WARNING:

This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Date of issue : 11/27/2018
Revision date : 11/27/2018
Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

11/27/2018 EN (English US) 6/6