



# MASONRY CEMENT TYPE S



Sakrete® Masonry Cement Type S is used to make mortar for laying brick, concrete block or stone in the construction of chimneys, walls, planters, outdoor grills and for pointing up or stuccoing old and new walls. Sakrete Masonry Type S meet the specifications for ASTM C91.

## Use For:

- Masonry cement for use in custom mortar mix

## Yield:

Bag Size	Standard Bricks	8" (416 mm) Blocks
75 lb (34 kg)	144	38
78 lb (35.4 kg)	150	40

## Color:

Gray

## Mixing:

Use the following mix proportions to make general purpose mortar:

Mix together

- 1 part of Masonry Cement or 1 ft<sup>3</sup> (2830 cm<sup>3</sup>)
- 3 parts masonry sand or general purpose sand.
- Add approximately 4.75 gal (18 L) of clean water. Mix until uniform, lump free consistency. Use the mortar within 1 hour after mixing.

*NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.*

## Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

**KEEP OUT OF REACH OF CHILDREN.**

## Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.